



DPS 200

Differential Pressure Transmitter for Gas and Compressed Air

Applications:

- ▶ for HVAC-applications

Characteristics:

- ▶ piezoresistive pressure sensor
- ▶ differential pressure range 1 ... 1000 mbar

Technical Data



Input pressure range							
Nominal pressure P _N [mbar] (differential, gauge pressure)	1	1.6	2.5	4	6	10	40
max. static pressure [mbar]	200	200	200	200	200	345	345
Nominal pressure P _N [mbar] (differential, gauge pressure)	60	100	160	250	400	600	1000
max. static pressure [mbar]	345	345	1000	1000	3000	3000	3000
Output signal / Supply							
Standard	3-wire: 0 ... 10 V			V _S = 19 ... 32 V _{DC} / 24 V _{AC} ± 10 %			
Option	3-wire: 0 ... 20 mA / 3-wire: 4 ... 20 mA			V _S = 19 ... 32 V _{DC} / 24 V _{AC} ± 10 %			
Performance							
Accuracy	1 % FSO BFSL						
Permissible load	current 3-wire: 330 Ω			voltage 3-wire: 10 kΩ			
Influence effects	supply: ≤ ± 0.1 % FSO			load: ≤ ± 0.1 % FSO			
Response time	adjustable by potentiometer in the range of 50 ms up to 2.5 s						
Measuring rate	1 kHz						
Thermal effects (Offset and Span) / Permissible temperatures							
Thermal error (offset and span)	0.5 % FSO / 10 K (typ.) for nominal pressure ≤ 5 mbar 0.3 % FSO / 10 K (typ.) for P _N > 5 mbar						
in compensated range	0 ... 50 °C						
Permissible temperatures	medium: 0 ... 50°C		electronics / environment: 0 ... 50°C		storage: -10 ... 70°C		
Electrical protection							
Short-circuit protection	permanent						
Reverse polarity protection	no damage, but also no function						
Elektromagnetic protection	emission and immunity according to EN 61326						
Materials							
Pressure port	brass nickel plated						
Housing	ABS						
Diaphragm	sensor						
Media wetted parts	pressure port, PVC / silicon tube, diaphragm, sensor						

DPS 200

Differential Pressure Transmitter

Technical Data

Miscellaneous	
Display (optional)	LC-Display, visible range 32.5 x 22.5 mm; 5-digit 7-segment-main display, digit size 8 mm, 8-digit 14-segment-additional display, digit size 5 mm; 52-segment-bargraph
Current consumption	signal output current: max. 30 mA signal output voltage: 7.5 mA (20 mA short circuit) display: + 1 mA
Ingress protection	IP 54
Weight	approx. 165 g
Installation position	vertical ¹
¹ The devices are calibrated in a vertical position with the pressure port down. If this position is changed on installation there can be slight deviations in the zero point.	
Mechanical connections (dimensions in mm)	
Standard	Ø 6.6 x 11 (for flex. tubes Ø 6)
Option	Ø 4.4 x 10 (for flex. tubes Ø 4)
Wiring diagram	
3-wire-system (current / voltage)	
Pin configuration	
Electrical connections	Terminals
supply +	2
supply -	3
signal +	1
Dimensions (in mm)	
<p>standard: DPS 200 without display</p>	
<p>optional: DPS 200 with display</p>	

This data sheet contains product specification, properties are not guaranteed. Subject to change without notice.

